

# PLEIAD G4



**Pleiad G4 Flex**

**Pleiad G4 70**

**Pleiad G4 125**

**Pleiad G4 165**

**Pleiad G4 205**

**Pleiad G4 Wallwasher**

**Pleiad G4 Robust**

**Pleiad G4 Square**

**Pleiad G4 Ytmonterad 128**

**Pleiad G4 Ytmonterad 168**

Håltagningsmått (mm)	110	70	125	165	205	165	205	165x165	128	168
Taktjocklek	5-50	5-50	5-50	5-50	5-50	0-35		5-50		
Max höjd	110	104	98	98	107	138	125	109	134	154
Low Lumen (LL)	790-829	790-830	1200	1300	1675	900	1100	1300	1000	1600
Medium Lumen (ML)				1800		1700	1600	1600	1400	2500
High Lumen (HL)	1400	1280	2350	2800	2800	2500	2600	3500	2400	4500
Extra High Lumen (EHL)				3700	5400					
Smalstrålande ~ 20°	●	●								
Medelstrålande 40-50°	●	●	●	●	●			●	●	●
Bredstrålande >70°			●	●	●		●	●	●	●
< UGR 19		●	●	●	●		●	●	●	●
< 3000 cd/m²		●	●	●	●		●	●	●	●
Blank reflektor						●				
Matt reflektor		●	●	●	●	●	●	●	●	●
Vit reflektor		●	●	●	●			●	●	●
Svart reflektor	●	●	●	●	●			●	●	●
2700 K / CRI 98 /SDCM 2		●								
3000 K	●	●	●	●	●	●	●	●	●	●
4000 K	●	●	●	●	●	●	●	●	●	●
CRI >80	●	●	●	●	●	●	●	●	●	●
CRI >90	●	●	●	●	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●	●	●	●	●
On/Off Standard	●	●	●	●	●	●	●	●	●	●
DALI/faspuls	●	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●	●		●
	Tilt 45° Turn 355°			Tunable White RGB/W Emergency	Tunable White Emergency	Tunable White RGB/W Emergency		Tunable White		Tunable White